

Company Advantages

At CobraFlex Printers we have professional state side, abroad ink R&D, production facility with multi-channel distributions with high output equipment manufacturing facility and comprehensive technical support.



Technical Parameters

Model	CobraFlex(NP) 24" & CobraFlex(NP) 50"		
Printhead	3pc *Epson i3200		
Printing Speed 24"	24" 320/2400 4pass 100sq Feet Per Hour	24" 720/1800 6 Pass 85sq Feet Per Hour	24" 720/2400 8 Pass 60sq Feet Per Hour
Printing Speed 50"	50" 320/2400 4pass 200sq Feet Per Hour	50" 720/1800 6 Pass 160sq Feet Per Hour	50" 720/2400 8 Pass 120sq Feet Per Hour
Color Mode	CYMKW & Special Printable Adhesive		
Printing Media	PET Transfer Film		
Media Transmission	Automatic Film Take Up		
Interface	Computer Included / USB3.0		
Ink Type	Eco Friendly Water Based Ink Ecotex Certified		
Ink System	Auto Circulation Supply System		
Power Printer	1 X 220V / 20 Amp		
Room Temperature	70° To 80° F		
Operating Environment	70° To 80° F		
Humidity	40% To 60%		
Power Dryer	1 X 220V 30 Amp Dedicated 24"	1 X 220V 30 Amp Dedicated 50"	
Footprint	CobraFlex(NP) 24"-89"X89"		CobraFlex(NP) 50"-105"X89"
Printer Weight	275 lbs		
Supplied	 		